



INDUSTRIAL TREATMENT



Controls the Build-up of Fats, Oils & Grease

Reduces Ammonia & Hydrogen Sulphide

Rapidly Breaks Down Organic Material

Eco-Friendly, Non-Hazardous & Non-Corrosive



**Australian
Owned**

DIRECTIONS FOR USE:

Dosage rates vary according to the application and area of use. Typical dosage rates for waste water are between 500 – 1000 ppm. For odour control and degradation of organic material, Industrial Treatment can be sprayed, fogged or misted directly onto the problem areas that are generating the odour. An authorised BioProtect® distributor should be consulted prior to use to determine the most effective program.

20 Litres



Batch Number:

Expiry Date:

MANUFACTURED BY:

Global BioProtect LLC
1/297 Ingles St, Port Melbourne,
VIC 3207 Australia.
Tel: 03 9646 9999

PRODUCT CODE: BPIT0020

HS CODE: 3402.90.00



**INTENDED FOR INDUSTRIAL USE.
FOR FURTHER INFORMATION REFER
TO THE SDS.**

**AUSTRALIA: IN AN EMERGENCY
CALL 000 NEW ZEALAND: IN AN
EMERGENCY CALL 111.**

**IF POISONING OCCURS, CONTACT A
DOCTOR OR POISONS INFORMATION
CENTRE. AUSTRALIA: CALL 13 11 26
NEW ZEALAND: CALL 0800 764 766.**

FIRST AID INFORMATION:

Eye Contact: Hold eyelids open and irrigate continuously with water for 15 minutes. Seek medical advice.

Skin Contact: Remove contaminated clothing. Wash affected areas with soap and water. Wash contaminated clothing before re-use.

Inhalation: Remove victim from exposure if safe to do so. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume a comfortable position and keep warm. Seek medical advice if symptoms persist.

Ingestion: Do NOT induce vomiting. Wash mouth out with water. Give water to drink. Seek medical advice.

STORAGE AND DISPOSAL:

Store below 40°C. Do not freeze. Non-refillable containers can be recycled or placed in trash receptacle. Do not mix with other products.